

MINFILE Number:	092HNE295	Name:	ELK (LAKE ZONE)	Status:	Prospect
------------------------	-----------	--------------	-----------------	----------------	----------

Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
DRILLHOLE			Gold	14.07 g/t	Drill hole SLD12-213 intersected a 19 centimetre wide quartz vein yielding 14.07 grams per tonne gold over 3.95 metres, including 89.8 grams per tonne gold over 0.3 metres. Assessment Report 34382
2012	N	Assay/analysis Drill Core			
DRILLHOLE			Gold	5.12 g/t	Drill hole SND11-149 intercepted a 1.2 metre interval, including 0.20 metre yielding 30.7 grams per tonne gold and 16.5 grams per tonne silver. Assessment Report 34382
2011	N	Assay/analysis Drill Core			
DRILLHOLE			Gold Silver	17.13 g/t 168.9 g/t	Diamond drilling yielded intercepts of 10.53 and 17.13 grams per tonne gold with 19.97 and 168.90 grams per tonne silver over 0.50 and 0.99 metre, respectively, in holes SLD05438 and SLD05439. Assessment Report 28203
2005	N	Assay/analysis Drill Core			
DRILLHOLE			Gold Silver	55.23 g/t 64.7 g/t	Drilling yielded intercepts of up to 55.23 grams per tonne gold and 64.7 grams per tonne silver over 0.55 metre in hole SLD-150 and 15.87 grams per tonne gold with 65.2 grams per tonne silver over 0.67 metre in hole SLD95-200. Assessment Report 24374
1995	N	Assay/analysis Drill Core			
DRILLHOLE			Gold	2.4300 g/t	Average grade over a true width of 2.0 metres. Assessment Report 21443, page 46.
1990	N	Assay/analysis Drill Core			
TRENCH			Gold	12.69 g/t	A panel sample of an argillic-altered pyritic dike exposed in trench SL89-1 assayed 31.1 grams per tonne gold over a true width of 0.86 metre. Later in the report a value of 12.69 grams per tonne over 0.86 metres is reported. Assessment Report 19835, page 2 and 42
1989	N	Assay/analysis Chip			