MINFILE Number: 082M 067 **Name:** ANACONDA **Status:** Prospect

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
DRILLHOLE 1990 N	Assay/analysis Drill Core	Copper Lead Zinc Silver Gold	0.92 % 0.37 % 3.30 % 25.0 g/t 0.10 g/t	a drill hole (BC-90-03), located approximately 500 metres to the north of the adit and at an elevation of 1175 metres, intersected an altered felsic volcanic breccia over 4.28 metres Assessment Report 21208
DRILLHOLE 1972 N	Assay/analysis Drill Core	Copper	0.85 %	diamond drilling on the area is reported to have yielded up to 0.85 per cent copper over 1.65 metres Assessment Report 8489
DRILLHOLE 1971 N	Assay/analysis Drill Core	Copper Zinc Lead	0.13 % 0.26 % 0.51 %	In 1990, re-logging of the 1970's Duncanex drill core yielded 0.21 and 0.13 per cent copper, 1.19 and 0.26 per cent zinc with 0.82 and 0.51 per cent lead over 2.14 and 15.85 metres in holes D71-5 and D71-7, respectively. No values for silver or gold are reported for these drill holes. Assessment Report 21208
DRILLHOLE 1952 N	Assay/analysis Drill Core	Copper Zinc Lead	0.27 % 0.17 % 0.02 %	drilling to the east of the adit is reported to have yielded intercepts of up to 0.55 per cent copper, 1.00 per cent zinc and 0.06 per cent lead over 0.6 metre in hole K-1; 1.40 per cent zinc over 0.4 metres and 0.50 per cent copper over 3.0 metres in hole K-2; 0.40 per cent copper and 1.40 per cent zinc over 0.6 metres and 0.60 per cent copper over 1.8 metres in hole K-3; 0.27 per cent copper, 0.17 per cent zinc and 0.02 per cent lead over 35.7 metres in hole K-4 and 0.36 per cent copper over 10.5 metres in hole K-5. No values for silver or gold are reported for these drill holes. Assessment Report 21208; Property File - Gower, S.C. [1976-11-01]: Geology Map of the Birk 1 and 2 Claims