

|                                 |                      |                                   |
|---------------------------------|----------------------|-----------------------------------|
| <b>MINFILE Number:</b> 082M 125 | <b>Name:</b> COMPLEX | <b>Status:</b> Developed Prospect |
|---------------------------------|----------------------|-----------------------------------|

| Ore Zone/<br>Year/Report On | Tonnage/<br>Category        | Commodity              | Grade                               | Reference/<br>Comments  |
|-----------------------------|-----------------------------|------------------------|-------------------------------------|---|
| B<br>2011                   | N<br>Assay/analysis<br>Rock | Lead<br>Zinc<br>Silver | 19.96 %<br>0.57 %<br>171 g/t        | four samples (545640 through 545643) for the area of the Bass shaft yielded values from 4.48 to 19.96 per cent lead, 0.05 to 0.57 per cent zinc and 48 to 171 grams per tonne silver<br>Williams, J.D. (2012-06-12): Technical Report on the Copper King – Cotton Belt Property |
| OUTCROP<br>1966             | Assay/analysis<br>Chip      | Silver<br>Lead<br>Zinc | 97.0000 g/t<br>5.3700 %<br>6.5100 % | Average of 21 surface chip samples across 1.4 metres along zone.<br>Property File (Report by A.R. Allen, 1966).   |
| B<br>1951                   | N<br>Assay/analysis<br>Chip | Lead<br>Zinc<br>Silver | 2.80 %<br>2.50 %<br>68.6 g/t        | a sample taken south east of the Bass shaft over 76.2 centimetres<br>Williams, J.D. (2012-06-12): Technical Report on the Copper King – Cotton Belt Property  |