

MINFILE Number: 083D 015	Name: BEND 2900	Status: Prospect
---------------------------------	------------------------	-------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
SOUTHEAST 1991 N	Assay/analysis Drill Core	Lead Zinc Silver	3.06 % 4.44 % 34.6 g/t	Four diamond drill holes (TK-91-1 to TK-91-4), totalling 1873.8 metres, were collard several hundred metres to approximately 1 kilometre to the south-southeast of the Bend 2900 zone to test the strike the extension of the zone. Intercepts included: 0.93 per cent lead, 2.45 per cent zinc and 14.4 grams per tonne silver over 2.7 metres (269.0 to 272.0 metres down-hole) in hole TK-91-1; 3.06 and 0.45 per cent lead, 4.44 and 2.01 per cent zinc with 34.6 and 9.3 grams per tonne silver over 0.4 and 1.3 metres, respectively (332.3 to 332.7 metres and 387.1 to 388.4 metres down-hole, respectively) in hole TK-91-3 and 0.76 per cent lead, 5.82 per cent zinc and 8.0 grams per tonne silver over 0.5 metre (441.3 to 441.8 metres down-hole) in hole TK-91-4 Assessment Report 22149
SOUTHWEST 1991 N	Assay/analysis Drill Core	Lead Zinc Silver	0.54 % 2.55 % 10.6 g/t	Three diamond drill holes (C91-1 to C91-3) were collard to the south-southwest of the Bend 2900 occurrence to test the down-dip extensions of the zone. Intersections included: 0.77 per cent lead, 2.40 per cent zinc and 11.9 grams per tonne silver over 5.48 metres (294.22 to 298.70 metres down-hole) in hole C91-1; 0.54 per cent lead, 2.55 per cent zinc and 10.6 grams per tonne silver over 11.2 metres (252.2 to 263.4 metres down-hole) in hole C91-2 and 0.31 per cent lead, 1.84 per cent zinc and 7.5 grams per tonne silver over 3.5 metres (336.9 to 340.4 metres down-hole) in hole C91-3 Assessment Report 21606
SAMPLE 1987 N	Assay/analysis Chip	Silver Lead Zinc	12.9000 g/t 1.2000 % 4.5000 %	Grades are weighted averages of five samples for all commodities except gold, over an average width of 4.7 metres. Assessment Report 16544.