

| | | |
|---------------------------------|-----------------------------|-------------------------|
| MINFILE Number: 092B 171 | Name: MONA-WESTHOLME | Status: Prospect |
|---------------------------------|-----------------------------|-------------------------|

| Ore Zone/ Year/Report On | Tonnage/ Category | Commodity | Grade | Reference/ Comments |
|-----------------------------|----------------------|-----------|----------|--|
| SAMPLE | | Copper | 20.90 % | three samples (one outcrop and two float) from the Mona and Westholme occurrence area yielded from 0.91 to 2.90 per cent copper, 0.01 to 0.57 per cent lead, 0.03 to 6.73 per cent zinc, 16 to 50 grams per tonne silver and 0.43 to 1.40 grams per tonne gold Assessment Report 40298 |
| | Assay/analysis | Zinc | 6.73 % | |
| 2021 | Grab | Silver | 50 g/t | |
| | | Gold | 1.40 g/t | |
| | | Lead | 0.57 % | |
| DRILLHOLE | | Copper | 0.49 % | 0.5 metre sample of core Assessment Report 18520 |
| | Assay/analysis | Silver | 5.8 g/t | |
| 1990 | Drill Core | | | |
| DRILLHOLE | | Copper | 0.49 % | drill hole MTS-63, located several hundred metres east-southeast of the Westholme shaft yielded 0.49 per cent copper and 5.8 grams per tonne silver 0.5 metre (277.40 to 277.90 metres down-hole) in intermediate tuff, ash, lithic tuff and chert hosting quartz veins with pyrite and minor chalcopyrite Assessment Report 18520 |
| | Assay/analysis | Silver | 5.8 g/t | |
| 1989 | Drill Core | | | |
| | | | | |
| | | | | |
| DRILLHOLE | | Copper | 0.136 % | drill hole MTS-64, located on the Nellena claim and approximately 650 metres southeast of the Westholme shaft, yielded intercepts including: 0.136 per cent copper with 0.465 per cent zinc over 0.20 metre (197.70 to 197.90 metres down-hole) and 0.7 per cent zinc over 0.55 metre (320.70 to 321.25 metres down-hole) Assessment Report 18859 |
| | Assay/analysis | Zinc | 0.465 % | |
| 1989 | Drill Core | | | |
| | | | | |
| | | | | |
| DRILLHOLE | | Copper | 2.96 % | drill hole MTS-65, located several hundred metres east of the Mona shaft, yielded intercepts including 2.96 per cent copper, 9.0 grams per tonne silver and 0.13 gram per tonne gold over 0.40 metre (329.40 to 329.80 metres down-hole) and 0.16 per cent copper, 0.49 per cent zinc, 6.0 grams per tonne silver and 0.14 gram per tonne gold with 0.26 per cent barium over 0.80 metre (423.10 to 423.90 metres downhole) Assessment Report 18859 |
| | Assay/analysis | Silver | 9.0 g/t | |
| 1989 | Drill Core | Gold | 0.13 g/t | |
| | | | | |
| | | | | |
| DRILLHOLE | | Zinc | 0.37 % | drill hole MTS-38, located east of the Westholme shaft, yielded intercepts of up to 0.37 per cent zinc with 0.14 gram per tonne gold over 1.00 metre (73.10 to 74.10 metres down-hole) from a felsic ash with chert fragments and beds hosting pyrite and trace chalcopyrite in veinlets Assessment Report 16716 |
| | Assay/analysis | Gold | 0.14 g/t | |
| 1987 | Drill Core | | | |
| | | | | |
| | | | | |

| Ore Zone/ Year/Report On | Tonnage/ Category | Commodity | Grade | Reference/ Comments |
|-----------------------------|-----------------------------------|--------------------------|--------------------------------|---|
| DRILLHOLE 1987 | N Assay/analysis Drill Core | Copper Silver Gold | 1.29 % 10.4 g/t 0.18 g/t | drill hole MTS-43, located west-southwest of the Mona shaft yielded intercepts including 1.29 per cent copper, 10.4 grams per tonne silver and 0.18 gram per tonne gold over 0.60 metre (130.50 to 131.10 metres down-hole) and 0.67 per cent copper over 0.80 metre (133.40 to 134.20 metres down-hole) in a felsar phyric crystal tuff/ash hosting semi-massive pyrite and chalcopyrite stringers Assessment Report 16716 |
| DRILLHOLE 1986 | N Assay/analysis Drill Core | Zinc Copper | 5.70 % 0.33 % | drill hole MTS-27, located between the Westholme and Mona shafts, was drilled to test an interpreted east continuation of the Lenora-Tyee mine horizon across the Fortuna faults and below the Mona diorite. Fine sphalerite stringers were encountered below the diorite within barium enriched, weakly sericitized quartz-crystal tuffs and yielded intercepts including 0.21 per cent zinc over 1.2 metres at 41.95 metres down-hole and 5.70 per cent zinc with 0.33 per cent copper over 0.07 metre at 52.42 metres down-hole Assessment Report 15719 |