

MINFILE Number:		Name:		Status:		
Ore Zone/ Year/Report On		Tonnage/ Category		Commodity	Grade	Reference/ Comments
DRILLHOLE				Silver	15 g/t	In 2009, four diamond drill holes, totalling 1,283.26
		Assay/analysis		Zinc	0.0877 %	metres, were completed on the Mag (P-12) zone. The
2009	N	Drill Core		Copper	8.7 %	best intersection was from Hole 9-11-G (sample
						G985502) which assayed 15 grams per tonne silver,
						0.0877 per cent zinc and 8.7 per cent copper over 0.42
						metre of skarn-altered dike rock with epidote, garnet,
						pyroxene, and vesuvianite (?) with about 35 per cent
						chalcopyrite rich sulphide in patches, bands and minor
						veinlets
						Assessment Report 31531
SAMPLE				Iron	55 %	In 2008, 6 of 7 samples from the Mag (P-12) zone
		Assay/analysis		Gold	2.53 g/t	assayed from 53 to 55 per cent iron, along with one
2008	N	Rock				sample (B279953) that assayed 2.53 grams per tonne
						gold
						Assessment Report 30394
REKO		4,500	kt	Iron	22 %	In 1975, Reako Explorations Ltd. reported an ore
		Inferred				reserve estimate on the Reko property (see Reko 3 --
1975	Y	Unknown				092C 090, Reko 38 -- 092C 110 and Reko 10 -- 092C
						091) of 4,500,000 tonnes grading 22 per cent iron
						George Cross News Letter No.207, 1975