

|                                 |                         |                         |
|---------------------------------|-------------------------|-------------------------|
| <b>MINFILE Number:</b> 092F 240 | <b>Name:</b> FAITH LAKE | <b>Status:</b> Prospect |
|---------------------------------|-------------------------|-------------------------|

| Ore Zone/<br>Year/Report On | Tonnage/<br>Category         | Commodity                | Grade                                   | Reference/<br>Comments   |
|-----------------------------|------------------------------|--------------------------|---|--|
| DISCOVERY<br>1987 N         | Assay/analysis<br>Grab       | Gold<br>Silver           | 37.71 g/t<br>274.6 g/t                  | sampling of the Discovery vein assayed up to 37.71 grams per tonne gold and 274.6 grams per tonne silver over 20 centimetres (sample AD01351)<br>Assessment Report 16866               |
| VEIN<br>1987 N              | Assay/analysis<br>Grab       | Gold<br>Silver           | 3.84 g/t<br>139.3 g/t                   | sampling of the Galena vein yielded up to 3.84 grams per tonne gold and 139.3 grams per tonne silver over 0.2 metres (sample AD01446)<br>Assessment Report 16866                       |
| SAMPLE<br>1987 N            | Assay/analysis<br>Grab       | Gold<br>Silver           | 167.45 g/t<br>72.3 g/t                  | Sampling of other veins, in the area, has yielded values up to 167.45 grams per tonne gold and 72.3 grams per tonne silver over 0.2 metres (sample AD01376)<br>Assessment Report 16866 |
| DRILLHOLE<br>1964 N         | Assay/analysis<br>Drill Core | Silver<br>Gold<br>Copper | 120.0000 g/t<br>24.6900 g/t<br>3.0000 % | From a 15 centimetre drill interval.<br>McDougall, J.J. (1964): Report on Faith Lake<br>Gold-Copper 1963.  |