

MINFILE Number: 092HNE053	Name: HIT	Status: Prospect
----------------------------------	------------------	-------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
MAIN		Gold	5.79 g/t	A 26-metre section in the southern part of the main exposed vein system was dominated by well-mineralized multi-episodic quartz veins that averaged 5.79 grams per tonne gold and 59.7 grams per tonne silver over an average horizontal width of 1.15 metres. A cut-off grade of 2.4 grams per tonne gold was used. Assessment Report 33024
2011	N Assay/analysis Chip	Silver	59.7 g/t	
VEIN		Gold	9.35 g/t	Average pf two select samples of quartz vein material. Assessment Report 28548
2006	N Assay/analysis Grab			
DRILLHOLE		Gold	0.60 g/t	Two angled drillholes intersected weakly pyritic quartz veins in weakly and erratically mineralized fault gouge and alteration zones, suggesting that the main quartz vein system has been displaced or warped into a steeper plane. Gold values in drill core ranged up to 0.60 gram per tonne. Assessment Report 22084, page 10
1991	N Assay/analysis Drill Core			
SOUTHWEST		Gold	0.002 g/t	Sample 12520 from a series of irregular limestone-hosted shears occur approximately 170 metres southwest of the south end of the prominent quartz vein system. Assessment Report 22084
1991	N Assay/analysis Rock	Silver	23.7 g/t	
		Copper	0.0499 %	
		Lead	0.791 %	
TRENCH		Gold	22.80 g/t	Furthest north trench (91-8) to expose bedrock yielded up to 22.80 grams per tonne gold and 48.6 grams per tonne silver over 2.0 metres. Assessment Report 22084
1991	N Assay/analysis Chip	Silver	48.6 g/t	
TRENCH		Gold	0.210 g/t	a trench (91-10), located approximately 100 metres east of the main trenched area, exposed a zone of shear related quartz veining yielding up to 0.210 gram per tonne gold over 2 metres Assessment Report 22084
1991	N Assay/analysis Chip			
TRENCH		Copper	0.139 %	Trench (91-33A), located approximately 1 kilometre south of the main trenched zone, yielded up to 0.139 per cent copper and 0.270 gram per tonne gold over two separate 2 metre sections. Assessment Report 22084
1991	N Assay/analysis Chip	Gold	0.270 g/t	
HIGH-GRADE		Gold	206 g/t	A grab sample (F5863) of heavily mineralized vein material. Assessment Report 21402
1990	N Assay/analysis Grab	Silver	321.4 g/t	
		Lead	3.86 %	

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
MAIN 1990	Assay/analysis Channel	Silver Gold	119.0000 g/t 12.3000 g/t	Average grade of main quartz vein system over a strike length of 109.7 metres and an average width of 1.4 metres. Assessment Report 21402, page 13, Figure 11.