

MINFILE Number: 092HNE157	Name: MISS	Status: Prospect
----------------------------------	-------------------	-------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
VEIN		Gold	9.96 g/t	A grab sample (662311) from the vein. Assessment Report 37685
	Assay/analysis	Silver	10.4 g/t	
2018	Grab	Lead	0.500 %	
		Zinc	0.301 %	
TRENCH		Silver	30.7000 g/t	Across 25 centimetres. Assessment Report 22084, Figure 13 (sample 12534).
	Assay/analysis	Gold	1.4600 g/t	
1992	Chip	Copper	0.0117 %	
		Lead	1.6696 %	
TRENCHES		Gold	1.46 g/t	Three trenches (91-23, -24 and -25), located south of hole 72412, exposed at least four north-trending, steeply east dipping banded sulphide (galena and sphalerite with minor chalcopyrite and pyrite) veins or vein structures, up to 1.5 metres wide, in a diorite. Chip samples (12529 and 12534) from trenches 91-25B and 91-24C yielded 1.66 and 1.46 grams per tonne gold, 19.7 and 30.7 grams per tonne silver with 0.743 and 1.670 per cent lead over 0.30 and 0.25 metre, respectively, while a grab sample (1231) over 4 metres from trench 91-25B yielded 0.147 per cent copper, 0.956 per cent lead, 74.9 grams per tonne silver and 1.050 grams per tonne gold. Assessment Report 22084, Figure 13
	Assay/analysis	Silver	30.7 g/t	
1991	Chip	Lead	1.670 %	
		Copper	0.0117 %	
		Lead	1.6696 %	
		Gold	1.4600 g/t	
		Silver	30.7000 g/t	
		Copper	0.0117 %	
		Lead	1.6696 %	
		Zinc	0.301 %	
NORTHEAST		Copper	0.507 %	Two samples (5842 and 5844) of shear related quartz veins with pyrite, chalcopyrite, galena and malachite, located on a steep east facing slope approximately 500 and 800 metres north-northeast of the main zone, yielded 0.507 and 0.459 per cent copper, 16.0 and 6.0 grams per tonne silver and 0.070 and 0.220 gram per tonne gold, respectively. Assessment Report 22084, Figure 5b
	Assay/analysis	Silver	16.0 g/t	
1991	Rock	Gold	0.070 g/t	
DRILLHOLE		Silver	5.8000 g/t	An angled drillhole (72412) analysed 0.785 gram per tonne gold, 14.9 grams per tonne silver, 0.03 per cent copper, 0.05 per cent lead and 0.17 per cent zinc over 1.22 metres (47.85 to 49.07 metres down-hole), while a second section of core from the same hole graded 0.049 gram per tonne gold, 5.8 grams per tonne silver, 0.9 per cent copper, 0.06 per cent lead and 0.8 per cent zinc over 2.05 metres (132.8 to 134.85 metres). Assessment Report 17243, page 5
	Assay/analysis	Gold	0.0490 g/t	
1987	Drill Core	Copper	0.9000 %	
		Lead	0.0600 %	
		Zinc	0.8000 %	
MAIN		Gold	0.050 g/t	A rock sample (RX38923) of mineralized quartz-siderite veinlets from the main occurrence area. Assessment Report 13755
	Assay/analysis	Silver	3.0 g/t	
1984	Rock	Copper	0.046 %	
		Lead	0.277 %	
		Zinc	0.715 %	

Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
1982	N	Assay/analysis Rock	Copper	0.328 %	A rock sample (RX042199) of altered and sheared basalt hosting small quartz veins with chalcopyrite, pyrite and malachite, taken west of a small wetland area and approximately 500 metres west-northwest of the main Miss occurrence. Assessment Report 10962
			Zinc	0.148 %	
1981	N	Assay/analysis Rock	Gold	0.075 g/t	A sample (RX42724) with siderite, pyrite and galena from the occurrence area. Assessment Report 10962
			Silver	8.1 g/t	
			Copper	0.052 %	
1981	N	Assay/analysis Rock	Copper	0.385 %	Sample (RX42722), taken west of a small wetland area and approximately 500 metres west-northwest of the main Miss occurrence. Assessment Report 10962
			Silver	3.3 g/t	