

MINFILE Number: 092HNE174	Name: CM	Status: Prospect
----------------------------------	-----------------	-------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
DRILLHOLE 1987	Assay/analysis Drill Core	Gold Silver	21.30 g/t 34.0 g/t	Diamond drilling yielded intercepts of up to 21.30 grams per tonne gold and 34.0 grams per tonne silver over 1.5 metres (36.0 to 37.5 metres down-hole) and 6.83 grams per tonne gold with 17.5 grams per tonne silver over 1.50 metres (43.5 to 45.0 metres down-hole) in hole 87-3, located near previous drill hole 83-8, while drilling approximately 200 metres to the south-southeast and in the area of the previous drill hole 86-5 yielded anomalous results of up to 0.25 gram per tonne gold over 16.5 metres (51.0 to 67.5 metres down-hole) in hole 87-9 and 0.45 gram per tonne gold over 4.5 metres (75.0 to 79.5 metres down-hole) in hole 87-10. Assessment Report 17523
DRILLHOLE 1986	Assay/analysis Drill Core	Silver Gold Copper	21.9400 g/t 4.4900 g/t 2.1000 %	A drill hole (86-5) on a zone of veined and altered volcanics, located approximately 200 metres south of the previous drill holes, analysed 4.49 grams per tonne gold, 21.94 grams per tonne silver, and 2.1 per cent copper over 2 metres (84 to 86 metres down-hole) of quartz-pyrite-chalcopyrite veining cutting volcanic conglomerate below the carbonaceous shale. Assessment Report 14983.
DRILLHOLE 1983	Assay/analysis Drill Core	Silver Gold Copper	411.0000 g/t 36.0000 g/t 0.2900 %	Drilling yielded up to 4.9 grams per tonne gold over 11.2 metres (39.6 to 51.8 metres down-hole), including 35.9 grams per tonne gold, 411 grams per tonne silver and 0.29 per cent copper over a 1.4 metre interval (42.6 to 44.0 metres down-hole) of pyritic argillite in hole 83-8. Assessment Report 12113.
DRILLHOLE 1967	Assay/analysis Drill Core	Gold Silver Copper	5.1 g/t 16.4 g/t 0.20 %	A diamond drill hole (DDH 1) yielded intercepts of 4.5, 5.1 and 3.9 grams per tonne gold, 39.3, 16.4 and 57.5 grams per tonne silver with 0.70, 0.20 and 0.26 per cent copper over 3.0, 18.0 and 3.0 metres (49.5 to 52.5, 63.0 to 81.0 and 93.0 to 96.0 metres down-hole), respectively. Assessment Report 13714, page 4