

<b>MINFILE Number:</b> 092HSW165	<b>Name:</b> FLEETWOOD	<b>Status:</b> Prospect
----------------------------------	------------------------	-------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
DRILLHOLE 1992	Assay/analysis Drill Core	Gold Copper Zinc	4.0000 g/t 2.2000 % 28.0000 %	From a 2 metre massive sulphide drill intersection in the 33 zone. Assessment Report 22915, page 7.
DRILLHOLE 1992	N Assay/analysis Drill Core	Zinc Copper Lead Silver Gold	23.30 % 1.83 % 1.71 % 133 g/t 2.33 g/t	drill hole (92-33) on the 33 zone over 3.20 metres (Allen, D.G. (2014-09-19): Technical Report on the Seneca VMS Project
DRILLHOLE 1991	N Assay/analysis Drill Core	Zinc Copper Lead Gold Silver	2.06 % 0.31 % 0.11 % 0.07 g/t 8.1 g/t	drilling on the Fleetwood zone over 32.1 metres, including 5.56 per cent zinc, 0.38 per cent copper, 0.37 per cent lead, 162 grams per tonne silver and 2.37 grams per tonne gold over 1.10 metres Allen, D.G. (2014-09-19): Technical Report on the Seneca VMS Project