

MINFILE Number: 092ISE106	Name: GOLD GOSSAN 2	Status: Showing
----------------------------------	----------------------------	------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
ADIT		Copper	0.57 %	a sample (SK-96) from a vein located at the entrance of the North adit Assessment Report 26468
	Assay/analysis	Lead	1.87 %	
2000	Grab	Silver	125.4 g/t	
		Gold	50.83 g/t	
TAILINGS		Copper	3.97 %	Two samples (SK-95A and -95B) of tailings from the South adit yielded 0.46 and 3.97 per cent copper, 20.7 and 130.2 grams per tonne silver with 0.225 and 0.972 gram per tonne gold Assessment Report 26468
	Assay/analysis	Silver	130.2 g/t	
2000	Grab	Gold	0.972 g/t	
SAMPLE		Gold	0.25 g/t	A rock sample (HOW-4) from the How 4 claim, located in the area of the occurrence Assessment Report 25744
	Assay/analysis	Silver	36.0 g/t	
1998	Rock	Copper	0.10 %	
DRILLHOLE		Copper	5.4 %	A drill hole (93-7), located approximately 400 metres to the northwest of the occurrence, intersected a narrow mineralized quartz vein yielding 5.4 per cent copper, 160 grams per tonne silver and 0.600 gram per tonne gold over 0.24 metre and porphyry style mineralization yielding 0.25 per cent copper, 8.7 grams per tonne silver and 0.260 gram per tonne gold over 2.46 metres Assessment Report 24600
	Assay/analysis	Silver	160 g/t	
1993	Drill Core	Gold	0.600 g/t	