

MINFILE Number:		Name:		Status:	
Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments	
FLOAT 2019	N	Gold Assay/analysis Grab	8.69 g/t	A select sample (J991890) of quartz vein float from the main Axel Ridge trenched zone. Assessment Report 38762	
PILE 3 2019	N	Gold Assay/analysis Grab	2.96 g/t	A sample (L995181) from the Dump Pile area. Assessment Report 38762	
ROAD 2019	N	Gold Assay/analysis Grab	3.24 g/t	A sample (L995192) from the Road zone. Assessment Report 38762	
ROAD 2007	N	Gold Assay/analysis Chip	0.60 g/t	A trench (PT07-05) located approximately 275 metres north-northwest of the main zone and on the Road zone, yielded 0.60 gram per tonne gold 38 metres, including 5.98 grams per tonne gold over 1.5 metres. Assessment Report 29633	
MAIN 2007	N	Gold Assay/analysis Chip	1.92 g/t	Trenching on the main Axel Ridge zone yielded values of 1.92 grams per tonne over 14 metres in trench PT07-02 and 1.05 grams per tonne gold over 4 metres in trench PT07-04. Assessment Report 29633	
MAIN 2006	N	Gold Assay/analysis Trench	2.83 g/t	Value from Trench 06-3 averaged over 6.6 metres, includes a section of 2.6 metres of 5.26 grams per tonne gold. http://almadenminerals.com , Assessment Report 28830	
FLOAT 2006	N	Gold Assay/analysis Grab	12.22 g/t Silver 44.5 g/t	Prospecting identified sub-angular float over a narrow, 100- to 700-metre wide, north-south trending structural and alteration corridor over an approximate 2500-metre strike length with 58 grab samples yielded from trace to 12.22 grams per tonne gold and averaging approximately 1.10 grams per tonne gold with silver values of up to 44.5 grams per tonne. Assessment Report 28830	