

MINFILE Inventory Detail Report BC Geological Survey

Ministry of Energy, Mines and Petroleum Resources

MINFILE	Number:	093J 035	Name: WES	ST WINDY	Status: Showing
Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
FLOAT 2016	N	Assay/analysis Grab	Gold Silver Copper	1.81 g/t 12.5 g/t 0.361 %	Samples of semi-massive to massive sulphide float boulders. Assessment Report 36209.
DRILLHOLE			Gold	2.271 g/t	Drill hole 08-05, located on the West Windy occurrence
2008	N	Assay/analysis Drill Core	Copper	0.125 %	area, intercepted a foliated diorite hosting quartz-sulphide veins and/or seams of massive pyrite and chalcopyrite yielding values of 0.810 gram per tonne gold over 3.0 metres (35.7 to 38.7 metres down-hole), 0.219 per cent copper and 0.255 gram per tonne gold over 0.9 metres (96.2 to 97.3 metres down), 0.326 per cent copper and 0.557 gram per tonne gold over 0.6 metres (118.8 to 119.4 metres down-hole) and 0.125 per cent copper with 2.271 grams per tonne gold over 0.5 metres (127.1 to 127.6 metres down-hole). Assessment Report 30754.
FLOAT 2004	N	Assay/analysis Grab	Copper Silver Gold	0.287 % 9.5 g/t 1.3 g/t	A second zone of massive sulphide boulders was identified, approximately 1 kilometre to the north of the West Windy occurrence. Two samples (R121 and R122) from the boulders. Assessment Report 28025.
NORTH	N	Assay/analysis Drill Core	Gold	0.191 g/t	Two diamond drill holes (90-5 and 90-6), located approximately 600 metres north-northeast of the West Windy occurrence, yielded intercepts including 0.175 and 0.240 gram per tonne gold over 5.9 and 4.3 metres, respectively, in hole 90-5, and 0.145 and 0.191 gram per tonne gold over 5.0 and 11.4 metres, respectively, in hole 90-6. Assessment report 21430.
TRENCH	N	Assay/analysis Chip	Gold Copper	6.010 g/t 0.440 %	Sampling of the trenches yielded values of up to 0.875 gram per tonne gold and 0.210 per cent copper over 5.2 metres of intensely altered and foliated andesite and 6.010 grams per tonne gold with 0.440 per cent copper over 1.3 metres of a faulted gouge zone in trench TR90-02.
TRENCH	N	Assay/analysis Chip	Gold Copper	0.185 g/t 0.084 %	Assessment Report 21430. Trench sampling yielded 0.185 gram per tonne gold with 0.084 per cent copper over 8.0 metres of fractured quartz diorite, including 1.56 gram per tonne gold with 0.330 per cent copper over 2.5 metres, along with two separate sections yielding 1.13 and 2.36 grams per tonne gold over 1.2 and 0.3 metres, respectively, in trench TR90-06. Assessment report 21430.