

<b>MINFILE Number:</b> 093J 035	<b>Name:</b> WEST WINDY	<b>Status:</b> Showing
---------------------------------	-------------------------	------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
FLOAT		Gold	1.81 g/t	Samples of semi-massive to massive sulphide float boulders. Assessment Report 36209.
	Assay/analysis	Silver	12.5 g/t	
2016	Grab	Copper	0.361 %	
DRILLHOLE		Gold	2.271 g/t	Drill hole 08-05, located on the West Windy occurrence area, intercepted a foliated diorite hosting quartz-sulphide veins and/or seams of massive pyrite and chalcopyrite yielding values of 0.810 gram per tonne gold over 3.0 metres (35.7 to 38.7 metres down-hole), 0.219 per cent copper and 0.255 gram per tonne gold over 0.9 metres (96.2 to 97.3 metres down), 0.326 per cent copper and 0.557 gram per tonne gold over 0.6 metres (118.8 to 119.4 metres down-hole) and 0.125 per cent copper with 2.271 grams per tonne gold over 0.5 metres (127.1 to 127.6 metres down-hole). Assessment Report 30754.
	Assay/analysis	Copper	0.125 %	
2008	Drill Core			
FLOAT		Copper	0.287 %	A second zone of massive sulphide boulders was identified, approximately 1 kilometre to the north of the West Windy occurrence. Two samples (R121 and R122) from the boulders. Assessment Report 28025.
	Assay/analysis	Silver	9.5 g/t	
2004	Grab	Gold	1.3 g/t	
NORTH		Gold	0.191 g/t	Two diamond drill holes (90-5 and 90-6), located approximately 600 metres north-northeast of the West Windy occurrence, yielded intercepts including 0.175 and 0.240 gram per tonne gold over 5.9 and 4.3 metres, respectively, in hole 90-5, and 0.145 and 0.191 gram per tonne gold over 5.0 and 11.4 metres, respectively, in hole 90-6. Assessment report 21430.
	Assay/analysis			
1990	Drill Core			
TRENCH		Gold	6.010 g/t	Sampling of the trenches yielded values of up to 0.875 gram per tonne gold and 0.210 per cent copper over 5.2 metres of intensely altered and foliated andesite and 6.010 grams per tonne gold with 0.440 per cent copper over 1.3 metres of a faulted gouge zone in trench TR90-02. Assessment Report 21430.
	Assay/analysis	Copper	0.440 %	
1990	Chip			
TRENCH		Gold	0.185 g/t	Trench sampling yielded 0.185 gram per tonne gold with 0.084 per cent copper over 8.0 metres of fractured quartz diorite, including 1.56 gram per tonne gold with 0.330 per cent copper over 2.5 metres, along with two separate sections yielding 1.13 and 2.36 grams per tonne gold over 1.2 and 0.3 metres, respectively, in trench TR90-06. Assessment report 21430.
	Assay/analysis	Copper	0.084 %	
1990	Chip			