

<b>MINFILE Number:</b>	093K 026	<b>Name:</b>	SILVER FOX	<b>Status:</b>	Past Producer
------------------------	----------	--------------	------------	----------------	---------------

Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
SAMPLE			Gold	15.5 g/t	A sample (no. 1) of mineralized quartz Assessment Report 13201
			Silver	20.6 g/t	
1984	N	Assay/analysis Rock			
SAMPLE			Gold	6.5 g/t	Assessment Report 10647
			Silver	6300 g/t	
			Lead	6.8 %	
			Zinc	9.8 %	
1982	N	Assay/analysis Rock			
DUMP			Gold	1.4 g/t	. A sample (71152) from the dump of the Silver Fox shaft Property File - 800790
			Silver	527 g/t	
			Copper	0.94 %	
1967	N	Assay/analysis Grab			
DRILLHOLE			Silver	2646.9000 g/t	Drill intersection over 2.1 metres. Minister of Mines Annual Report 1928, page 177.
			Gold	1.0300 g/t	
			Copper	1.9000 %	
			Zinc	5.1000 %	
1928	N	Assay/analysis Drill Core			
SHAFT			Gold	5.5 g/t	Sampling of the shaft yielded assays including 12.3 grams per tonne gold, 2320 grams per tonne silver, 1.2 per cent copper, 17.5 per cent lead and 13.8 per cent zinc over 0.48 metre at a depth of 36.0 metres and 5.5 grams per tonne gold, 8800 grams per tonne silver, 11.6 per cent lead and 12.5 per cent zinc over 0.38 metre at a depth of 42.0 metres Assessment Report 11584
			Silver	8800 g/t	
			Lead	11.6 %	
			Zinc	12.5 %	
1928	N	Assay/analysis Chip			
DRILLHOLE			Gold	1.03 g/t	a drill hole was completed on the 'High-grade' vein and at depths of 64.8 and 90.9 metres the drill intersection two 2.1 metre sections yielding 1.03 and 1.03 grams per tonne gold, 430.9 and 2646.9 grams per tonne silver, trace and 1.9 per cent copper, 7.8 and trace per cent lead with 2.4 and 5.1 per cent zinc, respectively Annual Report 1928, p.177
			Silver	2646.9 g/t	
			Copper	1.9 %	
			Zinc	5.1 %	
1927	N	Assay/analysis Drill Core			
DUMP			Silver	123.5 g/t	, a sample of adit dump material Property File Rimfire Windflower Mining Ltd., 1985
			Copper	1 %	
			Lead	3 %	
			Zinc	27 %	
1925	N	Assay/analysis Grab			