

MINFILE Number: 093K 026	Name: SILVER FOX	Status: Past Producer
---------------------------------	-------------------------	------------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
SAMPLE		Gold	15.5 g/t	A sample (no. 1) of mineralized quartz Assessment Report 13201
1984	Assay/analysis Rock	Silver	20.6 g/t	
SAMPLE		Gold	6.5 g/t	Assessment Report 10647
1982	Assay/analysis Rock	Silver	6300 g/t	
		Lead	6.8 %	
		Zinc	9.8 %	
DUMP		Gold	1.4 g/t	. A sample (71152) from the dump of the Silver Fox shaft Property File - 800790
1967	Assay/analysis Grab	Silver	527 g/t	
		Copper	0.94 %	
DRILLHOLE		Silver	2646.9000 g/t	Drill intersection over 2.1 metres. Minister of Mines Annual Report 1928, page 177.
1928	Assay/analysis Drill Core	Gold	1.0300 g/t	
		Copper	1.9000 %	
		Zinc	5.1000 %	
SHAFT		Gold	5.5 g/t	Sampling of the shaft yielded assays including 12.3 grams per tonne gold, 2320 grams per tonne silver, 1.2 per cent copper, 17.5 per cent lead and 13.8 per cent zinc over 0.48 metre at a depth of 36.0 metres and 5.5 grams per tonne gold, 8800 grams per tonne silver, 11.6 per cent lead and 12.5 per cent zinc over 0.38 metre at a depth of 42.0 metres Assessment Report 11584
1928	Assay/analysis Chip	Silver	8800 g/t	
		Lead	11.6 %	
		Zinc	12.5 %	
DRILLHOLE		Gold	1.03 g/t	
1927	Assay/analysis Drill Core	Silver	2646.9 g/t	a drill hole was completed on the 'High-grade' vein and at depths of 64.8 and 90.9 metres the drill intersection two 2.1 metre sections yielding 1.03 and 1.03 grams per tonne gold, 430.9 and 2646.9 grams per tonne silver, trace and 1.9 per cent copper, 7.8 and trace per cent lead with 2.4 and 5.1 per cent zinc, respectively Annual Report 1928, p.177
		Copper	1.9 %	
		Zinc	5.1 %	
DUMP		Silver	123.5 g/t	
1925	Assay/analysis Grab	Copper	1 %	, a sample of adit dump material Property File Rimfire Windflower Mining Ltd., 1985
		Lead	3 %	
		Zinc	27 %	