MINFILE Number: 093K 026 **Name:** SILVER FOX **Status:** Past Producer

Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
SAMPLE 1984	N	Assay/analysis Rock	Gold Silver	15.5 g/t 20.6 g/t	A sample (no. 1) of mineralized quartz Assessment Report 13201
SAMPLE 1982	N	Assay/analysis Rock	Gold Silver Lead Zinc	6.5 g/t 6300 g/t 6.8 % 9.8 %	Assessment Report 10647
DUMP 1967	N	Assay/analysis Grab	Gold Silver Copper	1.4 g/t 527 g/t 0.94 %	. A sample (71152) from the dump of the Silver Fox shaft Property File - 800790
DRILLHOLE 1928	N	Assay/analysis Drill Core	Silver Gold Copper Zinc	2646.9000 g/t 1.0300 g/t 1.9000 % 5.1000 %	Drill intersection over 2.1 metres. Minister of Mines Annual Report 1928, page 177.
SHAFT 1928	N	Assay/analysis Chip	Gold Silver Lead Zinc	5.5 g/t 8800 g/t 11.6 % 12.5 %	Sampling of the shaft yielded assays including 12.3 grams per tonne gold, 2320 grams per tonne silver, 1.2 per cent copper, 17.5 per cent lead and 13.8 per cent zinc over 0.48 metre at a depth of 36.0 metres and 5.5 grams per tonne gold, 8800 grams per tonne silver, 11.6 per cent lead and 12.5 per cent zinc over 0.38 metre at a depth of 42.0 metres Assessment Report 11584
DRILLHOLE 1927	N	Assay/analysis Drill Core	Gold Silver Copper Zinc	1.03 g/t 2646.9 g/t 1.9 % 5.1 %	a drill hole was completed on the ‘High-grade’ vein and at depths of 64.8 and 90.9 metres the drill intersection two 2.1 metre sections yielding 1.03 and 1.03 grams per tonne gold, 430.9 and 2646.9 grams per tonne silver, trace and 1.9 per cent copper, 7.8 and trace per cent lead with 2.4 and 5.1 per cent zinc, respectively Annual Report 1928, p.177
DUMP 1925	N	Assay/analysis Grab	Silver Copper Lead Zinc	123.5 g/t 1 % 3 % 27 %	, a sample of adit dump material Property File Rimfire Windflower Mining Ltd., 1985