

<b>MINFILE Number:</b>	093K 126	<b>Name:</b>	HANSON LAKE WEST	<b>Status:</b>	Prospect
------------------------	----------	--------------	------------------	----------------	----------

Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
TRENCH	2004	N	Assay/analysis Rock	Copper	Samples from historical trenches on the Kimura zone yielded up to greater than 1.00 per cent copper and 78.2 grams per tonne silver from a sample (VKO10-1a) of massive sulphides from trench 48. Assessment Report 27865).
				Silver	
DRILLHOLE	1990	N	Assay/analysis Drill Core	Copper	A 90-metre section of the Kimura zone graded 0.15 per cent copper and 0.012 per cent molybdenum sulphide. Property File Rimfire, Bruaset, R.V., 1991
				Molybdenum	
DRILLHOLE	1973	N	Assay/analysis Drill Core	Copper	In 1988, re-sampling of drill cuttings from the 1973 Placer Dome drilling yielded 0.1 per cent copper over 91.44 metres, including 0.10 to 0.12 per cent copper with 2.8 to 3.0 grams per tonne silver in three separate 3-metre intervals in hole P8, 0.1 per cent copper over 33.53 metres in hole P11, 0.1 per cent copper with 0.3 per cent zinc over 27.43 metres in hole P15 and 0.3 per cent zinc over 60.96 metres in hole P32. Assessment Report 18398 and 34832