

<b>MINFILE Number:</b>	093N 114	<b>Name:</b>	BIDDY	<b>Status:</b>	Prospect
------------------------	----------	--------------	-------	----------------	----------

Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
SAMPLE			Zinc	30 %	Samples 19BID-8 (outcrop), 19BID-9 (angular float) and 19BID -10 (outcrop) resulted in zinc values of 19.1, 24.4 and greater than 30.0 per cent, respectively, with samples 19BID-12 to -13 (outcrop) and 19Bid-14 to -17(angular float) showing zinc values of 14.85 per cent, 21.7 per cent, 7.49 per cent, 7.77 per cent, 6.31 per cent and 1.42 per cent, respectively. Sample 19BID-12 also yielded 5.15 per cent lead Assessment Report 38519
2019	N	Assay/analysis Rock			
DRILLHOLE			Lead	1.0000 %	A 2-metre drill interval from a drillhole in the Biddy area. Assessment Report 20492.
		Assay/analysis	Zinc	1.3000 %	
1990		Drill Core			
SAMPLE			Silver	28.0000 g/t	A grab sample from the Biddy area. Exploration in British Columbia 1989, page 195.
		Assay/analysis	Zinc	4.1100 %	
1988	N	Grab	Germanium	0.012 %	
SAMPLE			Zinc	4.57 %	Sample 19 Assessment Report 16946
		Assay/analysis			
1986	N	Grab			
TRENCH			Zinc	1.5 %	Within trench 13, sphalerite was noted to occur as orange grains and patches disseminated in either original porous zones, such as sandstones and arenaceous dolomite, with 1.5 per cent zinc across 10 metres (representing approximately 2.5 metres of true section), or as tectonically prepared porous-permeable zones such as the 'impregnated dolomite' breccia in the 'pit' area, with 1.2 percent zinc over 10 metres Assessment Report 16946
		Assay/analysis			
1986	N	Chip			
TRENCH			Zinc	3.5 %	An east-west fault cutting across the Centre pit showed 1.95 per cent zinc, 1.25 percent lead across 1 metre and, at the northern end of trench 45, resulted in zinc at 3.5 per cent Assessment Report 16946
		Assay/analysis			
1986	N	Rock			