

MINFILE Number: 093N 141	Name: WIT	Status: Developed Prospect
---------------------------------	------------------	-----------------------------------

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
DRILLHOLE 1995	Assay/analysis Drill Core	Gold Silver Lead Zinc	1.28 g/t 23.3 g/t 3.85 % 11.84 %	drilling yielded intercepts including 1.28 grams per tonne gold, 23.3 grams per tonne silver, 3.85 per cent lead and 11.84 per cent zinc over 3.5 metres in hole 01-01; 0.73 gram per tonne gold, 3.4 grams per tonne silver, 3.43 per cent lead and 5.29 per cent zinc over 2.0 metres in hole 01-02; 0.09 gram per tonne gold, 25.5 grams per tonne silver, 0.73 per cent lead and 2.05 per cent zinc over 2.0 metres in hole 01-03 and 72.2 grams per tonne silver, 0.11 per cent lead and 0.25 per cent zinc over 7.5 metres in hole 01-05 Assessment Report 24241
TRENCH 1995	Assay/analysis Chip	Gold Silver Zinc Lead	0.17 g/t 12.4 g/t 1.33 % 0.88 %	Trenching, in 1995, yielded values including 0.17 gram per tonne gold, 12.4 grams per tonne silver, 1.33 per cent zinc and 0.88 per cent lead over 22 metres in trench TR-141+50; 0.34 gram per tonne gold 22.9 grams per tonne silver, 3.43 per cent zinc and 5.97 per cent lead over 5 metres in trench TR-149; 0.380 gram per tonne gold, 21.1 grams per tonne silver, 0.82 per cent zinc and 0.12 lead over 5 metres in trench TR-146; 87.8 and 124.5 grams per tonne silver, 0.64 and 0.46 per cent zinc with 6.60 and 0.20 per cent lead over 3.0 metres each, respectively, in trench TR-149+50 and 0.137 and trace gram per tonne gold, 28.5 and 150.2 grams per tonne silver, 0.35 and 0.50 per cent zinc with 0.06 and 0.12 per cent lead over 3.5 and 4.0 metres, respectively, in trench TR-150 Assessment Report 24241
DRILLHOLE 1991	Assay/analysis Drill Core	Zinc Lead Silver	0.15 % 0.15 % 97 g/t	drilling yielded intercepts including 3.5 per cent zinc over 4 metres (66 to 70 metres down-hole), 0.15 per cent zinc, 0.15 per cent lead and 97 grams per tonne silver over 2 metres (70 to 72 metres down-hole) and 1.5 per cent zinc with 1.9 per cent lead over 2.5 metres (92.0 to 94.5 metres down-hole) in hole SK91-10 and 2.5 per cent zinc and 0.9 per cent lead over 2 metres (22 to 24 metres down-hole) in hole SK91-09. Gold values from the 1991 program were low, mostly between 0.2 and 0.6 gram per tonne, except for one value of 1.3 grams per tonne over 2 metres in hole SK91-10 Assessment Report 21820
TRENCH 1981	Assay/analysis Chip	Lead Zinc Silver	1.48 % 10.50 % 147.7 g/t	chip sampling of historic trenches yielded values of up to 0.30 per cent lead, 0.74 per cent zinc and 147.7 grams per tonne silver over 3.00 metres (sample 19207) and 1.48 per cent lead, 10.50 per cent zinc and 8.9 grams per tonne silver over 3.00 metres (sample 19210) Assessment Report 9705

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
WIT 1965 Y	20 kt Inferred	Lead Zinc	4.7000 % 2.3000 %	Combined lead-zinc is 7 per cent. The ratio of zinc to lead is not known and is here arbitrarily split 3:1 based on drill assays. Assessment Report 9705.