MINFILE Number: 094C 005 **Name:** SWANNELL **Status:** Prospect

Ore Zone/ Year/Report On	Tonnage/ Category	Commodity	Grade	Reference/ Comments
DRILLHOLE 2002 N	Assay/analysis Drill Core	Lead Zinc	0.68 % 2.97 %	In 2002, drillhole CS-02-14 intersected a graphitic fault zone containing low-grade sphalerite, galena and pyrite with crushed limestone fragments. The interval occurred from 64.4 to 65.4 metres. Assessment Report 27253.
DRILLHOLE 1985 N	Assay/analysis Drill Core	Zinc Lead Silver	5.83 % 1.29 % 15.3 g/t	Across 9.6 metres in drillhole CS-85-06 and includes 2.8 metres grading 12.04 per cent zinc, 0.99 per cent lead and 11.3 grams per tonne silver; from a 1985 drill program. Assessment Report 26702.
DRILLHOLE 1957 N	Assay/analysis Drill Core	Lead Silver Zinc	4.3 % 37.7 g/t 14.5 %	Across 1.7 metres in drillhole CS-57-01; results from a 1957 drill program. Assessment Report 26702.
SAMPLE 1954 N	Assay/analysis Grab	Silver Gold Lead Zinc	279.1000 g/t 0.6900 g/t 24.6000 % 27.4000 %	Geological Survey of Canada Memoir 274, page 210.