

| | | | | | |
|------------------------|----------|--------------|-------|----------------|----------|
| MINFILE Number: | 103B 009 | Name: | SWEDE | Status: | Prospect |
|------------------------|----------|--------------|-------|----------------|----------|

| Ore Zone/ Year/Report On | | Tonnage/ Category | Commodity | Grade | Reference/ Comments |
|-----------------------------|---|-------------------------------|-----------|-------------|---|
| EAST | | | Copper | 0.66 % | copper over an area of 180 by 180 metres on the Salmon Creek side of the peninsula |
| 1970 | N | Assay/analysis Bulk Sample | | | Property File - Ana Lake Mining Ltd. [1970-06-22]: Report - Brandy Mineral Claims |
| WEST | | | Copper | 0.30 % | covering an area 120 metres wide by 240 metres in length on the Anna Inlet side of the peninsula |
| 1970 | N | Assay/analysis Bulk Sample | | | Property File - Ana Lake Mining Ltd. [1970-06-22]: Report - Brandy Mineral Claims |
| ADIT | | | Silver | 20.5700 g/t | 4.5 metre sample from South Wall Adit. |
| 1967 | N | Assay/analysis Chip | Copper | 1.7000 % | Property File: Selnes, W.E., 1970, Figure 3A. |
| ADIT | | | Copper | 2.5 % | the three adits were sampled and assayed from 0.35 to 2.5 per cent copper and from 6.86 to 20.57 grams per tonne silver, with the south wall of the no.1 adit yielding up to 0.35 per cent copper and 8.6 grams per tonne silver over 9 metres, the south wall of the no.2 adit yielding 1.70 per cent copper and 20.5 grams per tonne silver over 4.5 metres and 2.05 per cent copper across 3.0 metres in the no.3 adit |
| 1967 | N | Assay/analysis Chip | Silver | 20.57 g/t | |
| | | | | | Property File - Selnes, W.E. [1970-12-02]: Prospectus - Ana Lake Mining Ltd. |
| OPENCUT | | | Copper | 0.5 % | an open-cut above the upper tunnel is reported to have yielded approximately 0.5 per cent copper over a length of 7.5 metres |
| 1956 | N | Assay/analysis Chip | | | Property File - E. Livingston [1956-01-01]: Geological Report on the Swede Group |
| EAST | | | Copper | 0.20 % | drilling is reported to have yielded: 0.75 per cent copper over 9.45 metres in hole no.1 and 0.66 per cent copper over 20.7 metres in hole no. 2, including 1.05 per cent copper over 8.25 metres, while another section assayed 2.1 per cent copper, 20.5 grams per tonne silver and 6.8 grams per tonne gold over 1.05 metres. The entirety of holes 1 and 2 averaged 0.12 per cent copper over 49.8 metres and 0.20 per cent copper over 115.8 metres, respectively. These holes were located on the Salmon Creek side of the peninsula. |
| 1916 | N | Assay/analysis Drill Core | | | Ana Lake Mining Ltd. [1970-12-06]: Prospectus - Ana Lake Mining Ltd.; Ana Lake Mining Ltd. [1988-12-06]: Prospectus - Ana Lake Mining Ltd. |