

MINFILE Inventory Detail Report BC Geological Survey

Ministry of Energy, Mines and Petroleum Resources

MINFILE	Number:	103B 009	Name: SW	EDE	Status: Prospect
Ore Zone/ Year/Report On		Tonnage/ Category	Commodity	Grade	Reference/ Comments
EAST 1970	N	Assay/analysis Bulk Sample	Copper	0.66 %	copper over an area of 180 by 180 metres on the Salmon Creek side of the peninsula Property File - Ana Lake Mining Ltd. [1970-06-22]: Report - Brandy Mineral Claims
WEST 1970	N	Assay/analysis Bulk Sample	Copper	0.30 %	covering an area 120 metres wide by 240 metres in length on the Anna Inlet side of the peninsula Property File - Ana Lake Mining Ltd. [1970-06-22]: Report - Brandy Mineral Claims
ADIT	N	Assay/analysis Chip	Silver Copper	20.5700 g/t 1.7000 %	4.5 metre sample from South Wall Adit. Property File: Selnes, W.E., 1970, Figure 3A.
ADIT		Assay/analysis	Copper Silver	2.5 % 20.57 g/t	the three adits were sampled and assayed from 0.35 to 2.5 per cent copper and from 6.86 to 20.57 grams per
1967	N	Chip			tonne silver, with the south wall of the no.1 adit yielding up to 0.35 per cent copper and 8.6 grams per tonne silver over 9 metres, the south wall of the no.2 adit yielding 1.70 per cent copper and 20.5 grams per tonne silver over 4.5 metres and 2.05 per cent copper across 3.0 metres in the no.3 adit Property File - Selnes, W.E. [1970-12-02]: Prospectus - Ana Lake Mining Ltd.
OPENCUT	N	Assay/analysis Chip	Copper	0.5 %	an open-cut above the upper tunnel is reported to have yielded approximately 0.5 per cent copper over a length of 7.5 metres Property File - E. Livingston [1956-01-01]: Geological Report on the Swede Group
EAST		Assay/analysis	Copper	0.20 %	drilling is reported to have yielded: 0.75 per cent copper over 9.45 metres in hole no.1 and 0.66 per cent copper
1916	N	Drill Core			over 20.7 metres in hole no. 2, including 1.05 per cent copper over 8.25 metres, while another section assayed 2.1 per cent copper, 20.5 grams per tonne silver and 6.8 grams per tonne gold over 1.05 metres. The entirety of holes 1 and 2 averaged 0.12 per cent copper over 49.8 metres and 0.20 per cent copper over 115.8 metres, respectively. These holes were located on the Salmon Creek side of the peninsula. Ana Lake Mining Ltd. [1970-12-06]: Prospectus - Ana Lake Mining Ltd.; Ana Lake Mining Ltd. [1988-12-06]: Prospectus - Ana Lake Mining Ltd.

Wednesday, April 9, 2025 MINFILE Number: 103B 009 Page 1 of 1